



## 2400L POWER AMPLIFIER

400 Watts  
RF Power  
For:

- Ultrasonic
  - Testing
  - Laboratory use
- 
- 10 KHz to 10 MHz
  - Instantaneous Bandwidth
  - 400 W 1dB Compression
  - Solid State
  - Air Cooled



The 2400L Amplifier is a rugged source of RF power, useful for ultrasonics, HF transmitters, RFI/EMI, plasma equipment and general laboratory applications. The 2400L represents E&I's commitment to providing RF power amplifiers of the highest quality, durability and ruggedness.

### **FLEXIBILITY:**

The 2400L produces 400 Watts of Class A linear power output over the entire frequency range from 10 KHz to 10 MHz. It has very low harmonic distortion along with low IMD products. Operation over the band is achieved without the need for any band switching or indeed any adjustments. The power gain is rated at 55 dB with a typical gain flatness of +/- 1.5 dB

The 2400L is compatible with most signal generators, frequency synthesizers, sweep generators and other laboratory signal sources. It accurately reproduces all waveforms within its power and frequency ranges: AM, FM, SSB, pulsed and other complex modulation schemes.

### **RUGGEDNESS:**

The 2400L is built to withstand a 13 dBm input (1.0 Volt RMS) for any VSWR load condition. The internal switched mode power supply is very conservatively rated, in order to facilitate operation over a large range of line conditions and temperatures. The forced air cooling provides for low internal temperatures, providing long term reliability. The RF power is delivered by rugged DMoS FETs, de-rated to provide for excellent MTBF figures.

# 2400L POWER AMPLIFIER

## Class of Operation

Class A

## Frequency Range

10 KHz to 10 MHz

## Rated Power Output

400 Watts (P1dB)

## Saturated Power Output

550 Watts Maximum

## Gain

55 dB (nominal)

## Gain Flatness

+/- 1.5 dB

## Input Power for rated Pout

1 mW

## Input Impedance / VSWR

50Ω / 1.5:1 maximum

## Output Impedance / VSWR

50Ω / 2:1 maximum

## Harmonic Level

< -21dBc

## Ruggedness

∞:1 VSWR

## Stability

Unconditional into any passive load

## Protection

Input: Unit will withstand input signal of +13 dBm without damage (1.0 V rms) max. and infinite load VSWR.

## Front Panel Display

Front panel indicates forward and reflected Power.

## Third Order Intercept Point

IP3 ~ 64 dBm

## AC Input

104 – 240 Volts 47-63 Hz

## Temperature Range

0 – 40 C

## Cooling

Forced air

## Weight

95 lbs (43 Kg)

## Dimensions (H x W x D)

13.0" x 16.5" x 18.1"

330.2 x 419 x 459.7 mm

ZYKANG

深圳众裕康科技有限公司  
Shenzhen Zhong Yu Kang Technology Co., Ltd

联系人：曾祥满 手机：13632925349 QQ：812401203 电话：0755-28896837

地址：深圳市龙岗区沙平北路111号6008 网址：www.zykang.cn 邮箱：zykang2021@163.com